



TYPE OF PROTECTION... Ex de FLAMEPROOF & INCREASED SAFETY  
 AREA CLASSIFICATION... ZONE 1 & 21, GAS GROUPS IIA & IIB  
 TO BS EN 60079-14  
 STANDARD... BS EN 50014/18/19  
 CERTIFICATE... EC TYPE EXAMINATION CERTIFICATE BASEEFA05ATEX0107  
 CODING... Ex II 2 GD EEx de IIB (refer to table for T Rating and Ambient)  
 INGRESS PROTECTION... IP66/67 TO BS EN60529  
 ENTRY... 2X M20 CABLE ENTRIES  
 INCOMING CABLE... UP TO 6mm<sup>2</sup> (3 CORE) FOR FOR LOOPING  
 BEAM TYPE... WIDE ANGLE  
 WINDAGE... 0.19 M sq

FLOODLIGHT MODEL	VOLTAGE	T CLASS	T Amb	WEIGHT KGS
285D/150/MS	220,230,240,254V 50HZ AVAILABLE	T4	55°C	28.5

DRAWN	DRAWN
CHECKED	
APPROVED	
DATE	

WITHOUT OUR PERMISSION THIS DRAWING, WHICH IS OUR COPYRIGHT, MAY NOT BE REPRODUCED OR MADE AVAILABLE TO THIRD PARTIES.  
 AUTHORIZATION IS GIVEN TO .....  
 TO REPRODUCE THIS DRAWING FOR INTERNAL PURPOSES ONLY.

DEF No	MOD BY	MATERIAL	CHANGE
		Material	
		Finish	Finish
		DIMS. IN	MM
		SCALE	-
		TOLERANCE	SEE
		SURFACE ROUGHNESS	
		DATE	
<b>Victor Lighting</b> Victor Lighting 388 Hillington Road, Glasgow G52 4BL, Scotland Tel:0141 810 9644 Fax:0141 810 9642			
Title 1 V164 EQUAL PLUS DRAWING NUMBER/SHEET NUMBER F2411 1 OF 1			