

General ordering data

Order No.	0904830000
Part designation	KLIPPONTB12 453820B/4S
Version	Housings, 458 mm, 200 mm, 382 mm
EAN	4032248631339
Qty.	1 pc(s).

Dimensions

Fixing dimension, height	305 mm
Fixing dimension, width	437 mm
Height	458 mm
Length	200 mm
Width	382 mm

General details

Cover fixing	M5 hexagon stainless-steel slotted screw + hinge
Enclosure fixing	External mountings with 11 mm holes
Integral fixing	M6 threaded stud
Resistance to shocks	10 J
Sealing material	Silicone (cover + flange)
Version cover	Hinge
Colour	shiny, electropolished
Surface finish	shiny, electropolished
Class of protection to EN 60529	IP 66 and IP 67
Weight	14,500 g
Ambient temperature, min.	-60 °C
Ambient temperature, max.	140 °C

Screwed cable glands top/bottom

M 12	81
M 16	55
M 20	24
M 25	21
M 32	12
M 40	10
M 50	4
M 63	3
Side of enclosure	Top / Bottom

Screwed cable glands, left/right

M12	87
M16	60
M20	27
M25	24
M32	12
M40	10
M50	4
M63	3
On housing side	left / right

Approvals

Approvals institutes

GOSTEX IEC EX IEC EX ATEX ATEX



Classifications

eClass 4.1	27-14-12-06
eClass 5.0	27-14-91-07
eClass 5.1	27-14-91-07

Similar products

Order No.	Part designation	Version
0904720000	KLIPPONTB12 453815B/1S	Housings, 458 mm, 150 mm, 382 mm
0904730000	KLIPPONTB12 453815B/2S	Housings, 458 mm, 150 mm, 382 mm
0904740000	KLIPPONTB12 453815B/3S	Housings, 458 mm, 150 mm, 382 mm
0904750000	KLIPPONTB12 453815B/4S	Housings, 458 mm, 150 mm, 382 mm
0904800000	KLIPPONTB12 453820B/1S	Housings, 458 mm, 200 mm, 382 mm
0904810000	KLIPPONTB12 453820B/2S	Housings, 458 mm, 200 mm, 382 mm
0904820000	KLIPPONTB12 453820B/3S	Housings, 458 mm, 200 mm, 382 mm