

General ordering data

Order No.	0905310000
Part designation	KLIPPONTB12C 453020B/4S
Version	Housings, 458 mm, 200 mm, 300 mm
EAN	4032248631742
Qty.	1 pc(s).

Dimensions

Fixing dimension, height	305 mm
Fixing dimension, width	355 mm
Height	458 mm
Length	200 mm
Width	300 mm

General details

Cover fixing	M5 hexagon stainless-steel slotted screw + hinge
Enclosure fixing	External mountings with 11 mm holes
Integral fixing	M6 threaded stud
Resistance to shocks	10 J
Sealing material	Silicone (cover + flange)
Version cover	Hinge
Colour	shiny, electropolished
Surface finish	shiny, electropolished
Class of protection to EN 60529	IP 66 and IP 67
Weight	12,500 g
Ambient temperature, min.	-60 °C
Ambient temperature, max.	140 °C

Screwed cable glands top/bottom

M 12	60
M 16	40
M 20	18
M 25	15
M 32	8
M 40	8
M 50	3
M 63	2
Side of enclosure	Top / Bottom

Screwed cable glands, left/right

M12	84
M16	58
M20	27
M25	24
M32	12
M40	10
M50	4
M63	3
On housing side	left / right

Approvals

Approvals institutes

GOSTEX IEC EX IEC EX ATEX ATEX



Classifications

eClass 4.1	27-14-12-06
eClass 5.0	27-14-91-07
eClass 5.1	27-14-91-07

Similar products

Order No.	Part designation	Version
0905200000	KLIPPONTB12C 453015B/1S	Housings, 458 mm, 150 mm, 300 mm
0905210000	KLIPPONTB12C 453015B/2S	Housings, 458 mm, 150 mm, 300 mm
0905220000	KLIPPONTB12C 453015B/3S	Housings, 458 mm, 150 mm, 300 mm
0905230000	KLIPPONTB12C 453015B/4S	Housings, 458 mm, 150 mm, 300 mm
0905280000	KLIPPONTB12C 453020B/1S	Housings, 458 mm, 200 mm, 300 mm
0905290000	KLIPPONTB12C 453020B/2S	Housings, 458 mm, 200 mm, 300 mm
0905300000	KLIPPONTB12C 453020B/3S	Housings, 458 mm, 200 mm, 300 mm