

General ordering data

| | |
|------------------|------------------------|
| Order No. | 0929030000 |
| Part designation | KLIPPONTB10 221513B/4S |
| EAN | 4032248628292 |
| Qty. | 1 pc(s). |

Dimensions

| | |
|--------------------------|--------|
| Fixing dimension, height | 152 mm |
| Fixing dimension, width | 208 mm |
| Height | 229 mm |
| Length | 133 mm |
| Width | 152 mm |

General details

| | |
|---------------------------------|--|
| Cover fixing | M5 hexagon stainless-steel slotted screw + hinge |
| Enclosure fixing | External mountings with 11 mm holes |
| Integral fixing | M6 threaded stud |
| Resistance to shocks | 10 J |
| Sealing material | Silicone (cover + flange) |
| Version cover | Hinge |
| Colour | shiny, electropolished |
| Surface finish | shiny, electropolished |
| Class of protection to EN 60529 | IP 66 and IP 67 |
| Weight | 4,500 g |
| Ambient temperature, min. | -60 °C |
| Ambient temperature, max. | 140 °C |

Screwed cable glands top/bottom

| | |
|-------------------|--------------|
| M 12 | 12 |
| M 16 | 14 |
| M 20 | 5 |
| M 25 | 2 |
| M 32 | 2 |
| M 40 | 1 |
| Side of enclosure | Top / Bottom |

Screwed cable glands, left/right

| | |
|-----------------|--------------|
| M12 | 17 |
| M16 | 18 |
| M20 | 3 |
| M25 | 3 |
| M32 | 2 |
| M40 | 2 |
| On housing side | left / right |

Approvals

Approvals institutes

GOSTEX IEC EX IEC EX ATEX ATEX



Similar products

| Order No. | Part designation | Version |
|-----------|------------------------|---------|
| 092900000 | KLIPPONTB10 221513B/1S | |
| 092901000 | KLIPPONTB10 221513B/2S | |
| 092902000 | KLIPPONTB10 221513B/3S | |