

General ordering data

Order No.	0929110000
Part designation	KLIPPONTB10A 262620B/4S
EAN	4032248630356
Qty.	1 pc(s).

Dimensions

Fixing dimension, height	170 mm
Fixing dimension, width	315 mm
Height	260 mm
Length	200 mm
Width	260 mm

General details

Cover fixing	M5 hexagon stainless-steel slotted screw + hinge
Enclosure fixing	External mountings with 11 mm holes
Integral fixing	M6 threaded stud
Resistance to shocks	10 J
Sealing material	Silicone (cover + flange)
Version cover	Hinge
Colour	shiny, electropolished
Surface finish	shiny, electropolished
Class of protection to EN 60529	IP 66 and IP 67
Weight	8,250 g
Ambient temperature, min.	-60 °C
Ambient temperature, max.	140 °C

Screwed cable glands top/bottom

M 12	27
M 16	54
M 20	22
M 25	15
M 32	8
M 40	6
M 50	2
M 63	2
M 75	1
Side of enclosure	Top / Bottom

Screwed cable glands, left/right

M12	21
M16	42
M20	16
M25	12
M32	6
M40	4
M50	2
M63	1
M75	1
On housing side	left / right

Approvals

Approvals institutes

GOSTEX IEC EX IEC EX ATEX ATEX



Similar products

Order No.	Part designation	Version
0929040000	KLIPPONTB10A 262615B/1S	
0929050000	KLIPPONTB10A 262615B/2S	
0929060000	KLIPPONTB10A 262615B/3S	
0929070000	KLIPPONTB10A 262615B/4S	
0929080000	KLIPPONTB10A 262620B/1S	
0929090000	KLIPPONTB10A 262620B/2S	
0929100000	KLIPPONTB10A 262620B/3S	