

**General ordering data**

Order No.	0929190000
Part designation	KLIPPONTB11 303020B/4S
EAN	4032248630615
Qty.	1 pc(s).

**Dimensions**

Fixing dimension, height	203 mm
Fixing dimension, width	455 mm
Height	306 mm
Length	200 mm
Width	306 mm

**General details**

Cover fixing	M5 hexagon stainless-steel slotted screw + hinge
Enclosure fixing	External mountings with 11 mm holes
Integral fixing	M6 threaded stud
Resistance to shocks	10 J
Sealing material	Silicone (cover + flange)
Version cover	Hinge
Colour	shiny, electropolished
Surface finish	shiny, electropolished
Class of protection to EN 60529	IP 66 and IP 67
Weight	10,000 g
Ambient temperature, min.	-60 °C
Ambient temperature, max.	140 °C

**Screwed cable glands top/bottom**

M 12	60
M 16	66
M 20	28
M 25	18
M 32	8
M 40	8
M 50	3
M 63	2
M 75	2
Side of enclosure	Top / Bottom

**Screwed cable glands, left/right**

M12	51
M16	54
M20	22
M25	15
M32	8
M40	6
M50	2
M63	2
M75	1
On housing side	left / right

## Approvals

Approvals institutes

GOSTEX IEC EX IEC EX ATEX ATEX



## Similar products

Order No.	Part designation	Version
0929120000	KLIPPONTB11 303015B/1S	
0929130000	KLIPPONTB11 303015B/2S	
0929140000	KLIPPONTB11 303015B/3S	
0929150000	KLIPPONTB11 303015B/4S	
0929160000	KLIPPONTB11 303020B/1S	
0929170000	KLIPPONTB11 303020B/2S	
0929180000	KLIPPONTB11 303020B/3S	